

SUNMI L2H Smart Mobile Terminal

Powerful PDA, higher, stronger and safer.

Octa-core Processor And SUNMI OS

With an octa-core processor inside and the 11nm manufacturing process adopted, L2H has been greatly improved in performance. The new SUNMI OS also brings you better design, smoothness and security.

Inbuilt Dual-band GPS And Barometer

Minimized position deviation. Locate your staff more accurately to a specific floor with the horizontal and vertical positioning system.

Barcode Reading And OCR*

In addition to reading 1D/2D barcodes (even if scratched, folded or stained), L2H also can recognize printed text with its OCR-enabled scanner.

*SUNMI provides you OCR SDK interfaces for quick and efficient OCR realization.

More Rugged And Durable

Featuring IP67 and 1.5m drop spec, L2H can stand harsh work environments with no compromise in performance.

Fingerprint Lock

Newly added fingerprint lock to protect your data.

*SUNMI provides you OCR SDK interfaces for quick and efficient OCR realization.



SUNMI L2H Tech Specs

Product Model T8911	OS SUNMI OS (*based on Android 11)	Processor Kyro-260 Octa-core (Quad Core, 2.0GHz+Quad Core, 1.8GHz)	Memory 4GB RAM+64GB ROM 6GB RAM+128GB ROM (optional)	Display 5.5" HD, 1440x720 Capacitive multitouch
Camera Front: 5MP FF Rear: 16MP AF Rear camera scanning 1D/2D barcode reading	NFC Reader Type A & B card, Mifare card, Felica card; ISO/IEC 14443 and ISO 15693 compliant	Scanner Professional scan engine (*optional Zebra & Honeywell)	Speaker 1* 1W	PSAM Card Slot 1* PSAM
Fingerprint Sensor Capacitive	vSIM Supports vSIM	Network 2G & 3G & 4G	Wi-Fi 2.4G/5G IEEE 802.11 a/b/g/n/ac/ax ready	Bluetooth Bluetooth 5.1 BLE
SIM Card Slot 1* Nano SIM 1* SIM	TF Card Slot 1* TF	GPS AGPS GPS/Glonass/Beidou/Galileo Support dual band L1/L5	Power Adapter Input: AC 100~240V Output: 5V/3A, 9V/2A	MIC 2* MIC
Buttons 1* Power (lock screen) button 2* Scan button 2* Volume (+/-) button 1* Custom button	Ports 1*Type-c, support OTG 2*pogo pin at the bottom for charging 8* pogo pin on the back for accessories	Battery Removable polymer lithium battery, 3.8V/5000mAh Non-removable polymer lithium battery, 3.7V/60mAh	Sensor G-Sensor Proximity sensor Light sensor Gyroscope E-compass Barometer	Dimensions (L*W*H) 154.4*74.6*17.1mm
Total Weight 245g	Protection IP67 1.5m drop spec *Certified by a third-party labs	Environment Operating temperature: -20°C~55°C Storage temperature: -40°C~70°C	Accessories (optional) Single charging base, Charging base, Trigger handle, UHF trigger handle, Hand strap (included), 4-slot charging base, 4-slot battery charger, Protective case, Screen tempered glass	

1.The usable memory may be less than the installed memory.
2.All specifications are subject to change without (prior) notice.



OFERTĂ RAPIDĂ

Ai găsit echipamentul potrivit?

Trimite-ne cerințele tale și primești o recomandare configurată pentru aplicația, volumul și bugetul companiei.

OFERTA TA ÎN 3 PAȘI

01

Trimite-ne cerința

Produs, SKU, cantitate sau descrierea aplicației.

02

Verificăm configurația

Compatibilitate, accesorii, stoc și termen de livrare.

03

Primești rapid oferta

Configurație clară, preț și suport pentru decizie.



Scanează pentru cererea de ofertă

autoid.ro/contact

CERE OFERTĂ

08008 288 643

contact@autoid.ro

L-V 9:00 - 17:00