

SUNMI T2s LITE Desktop POS

Flexible forms bring abundant experience

Performance breakthroughs on your fingertips.

High performance octa-core processor, up to 2.2Ghz. Equipped with large-capacity memory of 3GB RAM + 32GB ROM, T2s LITE allows you to experience unparalleled operation smoothness.

Anti-interference touch screen.

To realize your demand on worry-free touch experience in various environments, even near high-power devices, we employ an industrial-grade touch chip which is more resistant to EMI.

Unlock more possibilities with a VESA mount.

T2s LITE can be mounted with a VESA mount, enabling more applicable scenarios. For example, it can be used as a kitchen display of a KDS, greatly improving the restaurant operational efficiency.



Optional Accessories

NFC&MSR Card Reader

For NFC card reading and magnetic stripe card reading.



VESA mount

For more space-saving installation and more flexible use.



15.6"

Main: 15.6" FHD,
1920*1080



15.6" +10.1"

Main: 15.6" FHD,
1920*1080
Second: 10.1" HD,
1024*600



15.6" +15.6"

Main: 15.6" FHD,
1920*1080
Second: 15.6" FHD,
1920*1080



T2s LITE Tech Specs

Model Approved

Config 1: L1571 (Single-Display Version)
Config 2: L1572 (Dual-Display (small + big) Version)
Config 3: L1573 (Dual-Display (big + big) Version)

OS

Android 9.0
SUNMI OS

CPU

Kryo-260, Octa-core
up to 2.2GHz

Memory

32GB ROM + 3GB RAM
64GB ROM + 4GB RAM
(optional)

Camera

Face Recognition camera or
normal camera
(only for configuraion 2&3)

Display

Configuration 1: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen
Configuration 2: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen
Second: 10.1" HD, 1024*600 Capacitive multitouch screen
Configuration 3: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen
Second: 15.6" FHD, 1920*1080 Capacitive multitouch screen

Speaker

1* 1.2W

Bluetooth

BT2.1/3.0/4.0/5.0
BLE

Buttons

1* power button
2* volumn button

External Storage Card

Support Micro SD (TF)
Up to 64GB

SIM Card Slot

1* Micro SIM (optional)

LAN

LAN 100M

Network

2G&3G&4G (optional)

Wi-Fi

2.4G/5.0GHz
IEEE 802.11 a/b/g/n /ac

Interface

5* USB TypeA
1* RJ11 Serial port
1* RJ12 Cash drawer port
1* RJ45 LAN port
1* Audio jack
1* Power port
1* Micro-USB (debug)

Power Adapter

Input: AC100 ~ 240V/1.5A
Output: DC24V/1.5A

Dimensions

430*382*215mm
(max)

Weight

Configuration 1: 4.5 Kg
Configuration 2: 5.1 Kg
Configuration 3: 6.8 Kg

Environment

Operating temperature: 0°C ~ 40°C
Storage temperature: -20°C ~ 60°C

1.The usable memory may be less than the installed memory.

2.All specifications are subject to change without (prior) notice.



OFERTĂ RAPIDĂ

Ai găsit echipamentul potrivit?

Trimite-ne cerințele tale și primești o recomandare configurată pentru aplicația, volumul și bugetul companiei.

OFERTA TA ÎN 3 PAȘI

01

Trimite-ne cerința

Produs, SKU, cantitate sau descrierea aplicației.

02

Verificăm configurația

Compatibilitate, accesorii, stoc și termen de livrare.

03

Primești rapid oferta

Configurație clară, preț și suport pentru decizie.



Scanează pentru cererea de ofertă

autoid.ro/contact

CERE OFERTĂ

08008 288 643

contact@autoid.ro

L-V 9:00 - 17:00